


D2 CLUB

D2 club has been developed to provide an upgrade to polyester sheets and halyards offering the benefit of reduced mass and elongation thanks to the light weight Dyneema SK38 core. The strength and diameter of this rope is equivalent to typical polyester braids so it can be substituted without the complexity and expense of having to modify or change deck equipment like clutches and winches.



CORE MATERIAL:	Dyneema SK38				
	Continuous Filament High tenacity Polyester				
TESTING METHOD:	Apply check load according to BS EN ISO 2307 Measure sample length and weigh G/M according to BS EN ISO 2307 Measure rope pitch according to BS EN ISO 2307 Break in tensile testing machine (wedge grips)				
CONSTRUCTION					
CORE:	12 strand - 1 yarn per strand				
COVER:	16 plait over 1 under 1, 2 yarns per plait				
COLOURS:	blue, green, red and grey				

N.B. KNOTS WILL SIGNIFICANTLY REDUCE THE STRENGTH OF ANY ROPE. THIS PRODUCT WILL TYPICALLY RETAIN APPROXIMATELY 40% OF ITS STRENGTH IF TERMINATED WITH A KNOT. THE EXACT FIGURE WILL DEPEND ON THE TYPE OF KNOT USED AND OTHER FACTORS.

DIAMETER		M	ASS	AVERAGE STRENGTH			MIN STRENGTH		
mm	Inch	g/m	lb/100 ft	kg	lb	kN	kg	lb	kN
8	5/16	41.4	2.78	2190	4820	21.5	1970	4340	19.3
10	13/32	69.8	4.68	3780	8310	37.0	3400	7480	33.3
12	15/32	87.6	5.87	5200	11400	51.0	4680	10300	45.9
14	3/8	119.7	8.03	7400	16300	72.6	6660	14700	65.4

Marlow Ropes Ltd Ropemaker Park

Hailsham East Sussex, BN27 3GU England Marlow Ropes, Inc. Cordage Business Park Plymouth

MA 02360 USA www.marlowropes.com UK: +44 (0) 1323 444 444 sales@marlowropes.com US: +1 508 830 444 salesusa@marlowropes.com

Disclaime

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.

Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose.

Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

ISO 9001