Electric Winch Features Comparison Self-Tailing Electric Winches



	Features & Functionality												Included System Components O=Optional					
PRODUCT	1st Speed	2nd Speed	Variable Speed*	Additional Push Button (Repeater) Option**	Illuminated Push Button	Max. Load Cutout	Customised Load Cutout	Low Battery Cutout	Thermal Cutout	LED Status Alert	Load Output Signal	Polarity Check	Status Alerts Recording	Contactors/ Control Box	Circuit Breaker	Load Limiter	Push Button	Motor Input- Output Cable (Push Button Connection)
Andersen Compact Motor™			•	With initial order only	•	•			•	•			•	•	•	•	•	•
Andersen E1	•			Add any time	•	•	With initial order only	•	•	•	•	•		•	0	•	•	•
Andersen 2 Speed (78ST & 110ST)	•	•		Add any time	•	•	On request	•	•	•	•	•		•	0	•	•	•
Competitor A with type E control box (standard)	•			Add any time					•					•	•	N/A	•	N/A
Competitor A with ELS box	•			Add any time		•			•					•	•	•	•	N/A
Competitor B with electrical control box (standard)	•	•		Add any time										0	0	0	0	N/A
Competitor B with electrical control box and WLC box	•	•		Add any time		•	With initial order only							0	0	N/A	0	N/A

^{*} Compact Motor™ speed is proportional to the finger pressure applied to the push button.



^{**} Additional push button can be added anytime by connecting in parallel, unless switches are digital.

Where digital switches are used (e.g. Compact Motor™ winches) the additional push button (available for all sizes 28ST-62ST) must be specified with the original order.

Information for non-Andersen product above is as per the manufacturers' website or catalogue at time of publishing.