## DATASHEET

## **EXCEL R8**

This new rope within the Excel range compliments the existing fusion family of products, using a Dyneema® SK78 core but with an 8 plait cover, blended from Technora® aramid and polyester.

Available in 4mm and 5mm diameters where it excels as a halyard working on cleats, and 7mm and 8mm where it works as a high performance sheet performing well in ratchet blocks.



**APPLICATIONS:** 

**MATERIAL** 

CORE:

**COVER:** 

Halyards, Spinnaker halyards and sheets

Dyneema® SK78 12 strand

8 plait Technora®/polyester blended cover

## **PERFORMANCE**

DIAMETER		MASS			AV. BREAKLOAD		MIN STRENGTH		
mm	Inch	g/m	lb /100ft	kg	lb	kN	kg	lb	kN
4	5/32	10.8	0.72	893	1670	8.8	804	1770	7.9
5	3/16	16.5	1.11	1200	2650	11.8	1080	2390	10.6
7	1/4	27.5	1.84	1620	3560	15.8	1450	3200	14.3
8	5/16	44.5	2.98	2550	5610	25.0	2290	5050	22.5

Marlow Ropes Ltd

Ropemaker Park Hailsham East Sussex, BN27 3GU England

Marlow Ropes, Inc. Cordage Business Park Plymouth MA 02360 USA

www.marlowropes.com UK: +44 (0) 1323 444 444 sales@marlowropes.com US: +1 508 830 444 salesusa@marlowropes.com

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied. Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability

and fitness for a particular purpose.

Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines. Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.





Certification Number 315 ISO 9001