

Marlow ^{DATASHEET}®

HARDY HEMP

Soft handling and a “hairy look and feel” mean this rope has the authentic look of natural fibre. However, being made from polypropylene, Hardy Hemp gives all the aesthetics qualities of natural fibre but with the benefits of modern technology - floats, non-rot, UV resistant.



APPLICATIONS:	Mooring
CONSTRUCTION	
CONSTRUCTION:	3 Strand Polypropylene
COLOURS:	Natural
LENGTHS:	100m, 200m
PROPERTIES:	Floats Very easily spliced Natural fibre effect without rotting

PERFORMANCE

DIAMETER	WEIGHT	AV. BREAK LOAD	MIN BREAK LOAD
mm	kg/100m	kg	kN
6	1.50	390	2.94
8	2.80	640	4.90
10	4.50	1030	9.32
12	6.20	1470	13.34
14	8.10	2020	18.73
16	11.7	2870	24.52
18	14.0	3330	31.09
20	19.4	4470	41.38
24	26.3	5940	48.35

Marlow Ropes Ltd
Ropemaker Park
Hailsham
East Sussex, BN27 3GU
England

Marlow Ropes, Inc.
Cordage Business Park
Plymouth
MA 02360
USA

www.marlowropes.com
UK: +44 (0) 1323 444 444
sales@marlowropes.com
US: +1 508 830 0444
salesusa@marlowropes.com

Disclaimer

Marlow Ropes Ltd endeavours to ensure that all products are manufactured to the highest standard, these guidelines are not intended and do not create any warranties, express or implied.
Marlow Ropes Ltd expressly disclaims warranties or representations of any kind, express or implied, including the implied warranties of merchantability and fitness for a particular purpose.
Marlow Ropes Ltd shall not be liable for any consequential, incidental or contingent damages whatsoever stemming from the use of these guidelines.
Marlow Ropes Ltd has a policy of continual improvement which may result in specification and colour changes without prior notice.

MA-DA-076 | ISSUE NO.2



Certification Number 315
ISO 9001